

TECHNICAL DATA SHEET

LT 7040



Komplet's LT7040 mobile compact crusher offers speed, maneuverability, portability and ease of operation. Hydraulic jaw inlet adjustments, vibrating grizzly feeder, foldable extracting conveyor belt, and a second speed make it an ideal solution for recycling and crushing.

STANDARD FEATURES
<ul style="list-style-type: none"> • Autec remote control for all functions • Inspection ladder • Side protection
ACCESSORIES
<ul style="list-style-type: none"> • Magnetic belt with optional lifting system • Dust control system • Jaw box overfeeding sensor system • Spotlight 12v

ISUZU WATER COOLED TURBO DIESEL ENGINE		
Power	Hp	70
Cylinder	Qty	4
Fuel Capacity	Gal	52.8
Consumption	Gal / h	4.25
Fuel Type	Diesel	
Cooling	Water	
PERFORMANCE*		
Production	T / h	10 - 120
Max Size	in.	24
Standard Weight	lbs	26,500
*The production performance is dependent on the type and volume of material being processed as well as the size of the material produced.		
WEIGHTS & DIMENSIONS		
MACHINE	Operation	Transport
Length (ft & in)	26' 9"	18' 5"
Width (ft & in)	7' 5"	7' 5"
Height (ft & in)	8' 10"	8' 10"
RUBBER TRACKS		
Length	ft & in	9' 1"
Width	ft & in	1' 4"
Speed	1 st 0.4 mph	2 nd 1.4 mph
JAW CRUSHER		
Crusher Dimension	in	27" x 16"
Jaw Adjustment	Hydraulic	
Granulometry	in	3/4" - 4"
FEEDING / GRIZZLY WITH HOPPER		
Length	ft & in	7' 11"
Width	ft & in	5' 2"
Hopper capacity	yd ³	3
Loading Height	ft & in	8' 10"
FOLDING EXTRACTING BELT		
Length	ft & in	20' 10"
Width	ft & in	2' 8"
Discharge Height	ft & in	5' 11"