

TECHNICAL DATA SHEET

SC 221



Komplet's track mounted screener SC221 is the smallest self-propelled screening plant on the market today. Lightweight, compact and robust, it is designed for construction and demolition, excavations, compost, asphalt, rock, and more. It is fully remote controlled so a single operator can carry all operations of feeding and screening.

| STANDARD FEATURES |
|--|
| <ul style="list-style-type: none"> Autec remote control for all movements |
| ACCESSORIES |
| <ul style="list-style-type: none"> Side protection |

| ISUZU MOTOR | | |
|--|-----------|---------------|
| Power | Hp | 28.5 |
| Cylinder | Qty | 3 |
| Fuel Capacity | Gal | 10.5 |
| Consumption | Gal / h | 1.45 |
| Fuel Type | Diesel | |
| Cooling | Water | |
| PERFORMANCE* | | |
| Production | T / h | 80 |
| Max Size | in. | 0 - 10 |
| Standard Weight | lbs | 7,055 |
| <i>*The production performance is dependent on the type and volume of material being processed as well as the size of the material produced.</i> | | |
| WEIGHTS & DIMENSIONS | | |
| MACHINE | Operation | Transport |
| Length (ft & in) | 12' 2" | 12' 2" |
| Width (ft & in) | 5' 3" | 5' 3" |
| Height (ft & in) | 7' 4" | 7' 4" |
| RUBBER TRACKS | | |
| Length | ft & in | 6' 11" |
| Width | ft & in | 12" |
| TRACKED VIBRATING SCREEN | | |
| Dimension grid | ft & in | 7' 3" x 3' 4" |
| Screening grid | Qty | 2 |
| FINE MATERIAL BELT** | | |
| Length | ft & in | 9' 11" |
| Width | ft & in | 3' 4" |
| Discharge Height | ft & in | 5' 10" |
| <i>**Placed under the deck. Extra belt for right or left discharge fine material.</i> | | |
| MEDIUM MATERIAL BELT | | |
| Length | ft & in | 8' 3" |
| Width | ft & in | 1' 4" |
| Discharge Height | ft & in | 3' 8" |